



CountryMark®

**Advantage™**

**LUBRICANTS**

*Pour in the  
Advantage...*

*Multi-Vehicle*  
**Automatic**  
**Transmission**  
*Fluid*

*Anti-Wear*

*Anti-shudder Bonus*

*Smooth Shifting*

*...and pour on the heavy traffic.*

CountryMark's Advantage™ Multi-Vehicle Automatic Transmission Fluid is specially formulated using synthetic base stocks, seal conditioner, and other performance additives to exceed the performance and protection requirements of newer and rebuilt transmissions. Installers can rely on this single fluid to conveniently and accurately meet a wide array of global OEM requirements in North America. It includes most GM, Ford, Chrysler, Jeep Saturn, Honda/Acura, Toyota, Nissan, Mitsubishi, Hyundai, Mercedes, BMW, VW/Audi, and other transmissions. Always check the owner's manual for details. Strong anti-wear additives provide protection of transmission parts for longer life. In addition, good compatibility with seal material minimizes leaks. It contains a polymer additive that provides shear stability and minimizes oil viscosity change over a wide temperature range.

### Applications

CountryMark Advantage Multi-Vehicle Automatic Transmission Fluids are formulated to meet or exceed engine manufacturers' specifications and requirements.

Exceeds performance requirements:

- DEXRON® - III H / MERCON® FLUID
- MERCON® V

Meets performance requirements:

- MERCON® SP AND MERCON® LV
- DEXRON® VI
- CHRYSLER ATF+3 AND CHRYSLER ATF+4

Also suitable for use in:

- ALLISON C-4, TES-389
- NISSAN & INFINITY MATICK J/K
- TOYOTA AND LEXUS JWS 3309/TYPE T IV/ TYPE WS
- HONDA AND ACURA ATF-Z1
- HYUNDAI SP II/ SPIII
- AUDI PART #G 052 025-A2
- MERCEDES-BENZ, PAGE 236.9
- VOLVO PART#1161540-8
- ZF TE-ML 03D/ 04D/ 09/ 14A/ 14B/ 17C

### Features and Benefits

**Capability:** Formulated to meet the stringent frictional and viscosity requirements of most automatic transmissions from 1983 to the current model year.

**Friction Retention:** Uniquely balanced frictional properties provide anti-shudder durability, smooth shifting, and precise lockup throughout the service interval.

**Operability:** Improved cold temperature flow characteristics assure ease of pumping, quick start-up and smooth shifting, even at extremely low temperatures.

Properties	Test	Advantage Multi-Vehicle
Viscosity, cSt @ 40°C	D445	34.1
@ 100°C	D445	7.9
Viscosity Index	D2770	219
Brookfield @ -40		cP 9000
API Gravity/Lbs gal		34.1/7.1
Pour Point °C	D97	°F -58
Flash Point		°F 375
Color	Visual	Red

### Contact

For additional information, call CountryMark Technical Support at 1-800-537-5303 and visit us online at [www.countrymark.com](http://www.countrymark.com).

### Packaging

Available in quarts, pails, drums, totes & bulk.

Get more per gallon.™



CountryMark®