



MATERIAL SAFETY DATA SHEET

COUNTRYMARK ADVANTAGE EXTREME TACKY GREASE

1. PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME COUNTRYMARK ADVANTAGE EXTREME TACKY GREASE

PART No. GR-3-1, GR-3-2, GR-3-3

PRODUCT USE Lubricating Grease

SUPPLIER Metalcote Division of Chemtool Incorporated
P.O. Box 538
8200 Ridgefield Road
Crystal Lake, IL 60039-0538 USA
Tel: (815) 459-1250
Fax: (815) 459-1955

EMERGENCY TELEPHONE Infotrac
U.S. and Canada - (800) 535-5053
Outside the U.S. and Canada - +01-352-323-3500

Date of last issue 2006-09-05

2. COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
DISTILLATES, PETROLEUM, REFINED HEAVY NAPHTHENIC (CAS 64741-96-4 OR 64742-52-5)	Variable	50-70 %
RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED	64741-95-3	10-30 %
*OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	7620-77-1	5-12 %
LIMESTONE (CALCIUM CARBONATE)	1317-65-3	1-5 %
*PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	68649-42-3	0.5-1.5 %

* This chemical(s) is hazardous according to OSHA/WHIMIS criteria

COMPOSITION COMMENTS Refer to section eight for exposure limits on ingredients.
Chemical ingredients not regulated by OSHA, SARA, state or federal agencies are treated confidentially.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Exposure to vapors generated at high temperatures may cause respiratory irritation. Not regarded as a health hazard under current legislation.

SENSITIZATION

No known information.

CARCINOGENICITY

IARC: Not listed as a Group 1, 2A, or 2B agent. OSHA: Not regulated. NTP: Not listed.

TERATOGENICITY

No data available to indicate product or any components contained at greater than 0.1% may cause birth defects.

HEALTH WARNINGS

INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. Slightly irritating. INGESTION. Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact. Ingestion.

4. FIRST AID MEASURES

INHALATION

Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product, immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

EYES

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.

SKIN

Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Get medical attention immediately!

5. FIRE FIGHTING MEASURES

FLASH POINT (°C)

224 (435°F) Cd OC (Cleveland open cup).

FLAMMABILITY LIMIT - LOWER(%)N/D

FLAMMABILITY LIMIT - UPPER(%)N/D

EXTINGUISHING MEDIA

Use: Carbon dioxide (CO₂). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Pressure will increase in over heated, closed containers.

HAZARDOUS COMBUSTION PRODUCTS Acrid smoke/fumes. Oxides of: Carbon. Sulfur.

PROTECTIVE MEASURES IN CASE OF FIRE Self-contained breathing equipment and chemical resistant clothing recommended.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Minimize skin contact.

PRECAUTIONS TO PROTECT THE ENVIRONMENT Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

SPILL CLEAN-UP PROCEDURES Keep all sources of ignition and hot metal surfaces away from spill. Avoid contact with eyes or skin. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use absorbant material. Avoid discharge to natural water ways.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.

STORAGE CRITERIA Chemical storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
DISTILLATES, PETROLEUM, REFINED HEAVY NAPHTHENIC (CAS 64741-96-4 OR 64742-52-5)	OSHA			5 mg/m3 (oil mist)	
	ACGIH			5 mg/m3 (oil mist)	10 mg/m3 (oil mist)
RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED	OSHA			5 mg/m3 (oil mist)	
	ACGIH			5 mg/m3 (oil mist)	10 mg/m3 (oil mist)
LIMESTONE (CALCIUM CARBONATE)	OSHA	15 mg/m3 (total)		5 mg/m3 (resp)	
	ACGIH			10 mg/m3	** (e)

INGREDIENT COMMENTS **ACGIH (e): Total dust, containing no asbestos and <1% crystalline silica

PROTECTIVE EQUIPMENT



ENGINEERING CONTROLS	Use engineering controls to reduce air contamination to permissible exposure level.
VENTILATION	No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.
RESPIRATORS	No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.
PROTECTIVE GLOVES	Chemical resistant gloves recommended to prevent prolonged or repeated contact. Use protective gloves made of: Neoprene, nitrile, polyethylene or PVC. or latex.
EYE PROTECTION	Use eye protection.
PROTECTIVE CLOTHING	Wear appropriate clothing to prevent repeated or prolonged skin contact.
HYGIENIC WORK PRACTICES	Wash at the end of each work shift and before eating, smoking and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE	Grease.		
COLOR	Amber.		
ODOR	Mild (or faint). Petroleum.		
SOLUBILITY DESCRIPTION	Insoluble in water.		
DENSITY	0.90	Temperature (°C)	15.6 (60°F)
VAPOR DENSITY (air=1)	> 5		
VAPOR PRESSURE	< 0.1 mmHg	Temperature (°C)	20 (68°F)
EVAPORATION RATE	< 1	Reference	BuAc=1

10. STABILITY AND REACTIVITY

STABILITY	Normally stable.
CONDITIONS TO AVOID	Avoid contact with acids and oxidizing substances.
HAZARDOUS POLYMERIZATION	Will not occur.
POLYMERIZATION DESCRIPTION	Not applicable
HAZARDOUS DECOMPOSITION PRODUCTS	Oxides of: Carbon. Sulfur.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION No experimental toxicological data on the preparation as such is available.

COMPONENT	DISTILLATES, PETROLEUM, REFINED HEAVY NAPHTHENIC (CAS 64741-96-4 OR 64742-52-5)
TOXICOLOGICAL DATA	Carcinogenicity. IP 346 <3% Corrosive effects. Eye. Rabbit. < 15/110 Corrosive effects. Skin. Rabbit. < 0.5/8
TOXIC DOSE - LD 50	> 5000 mg/kg (oral rat)
TOXIC DOSE - LD 50 SKIN	> 3000 mg/kg (skn rat)
TOXIC CONC. - LC 50	N/A.
CARCINOGENICITY	Base oils in this product contain < 3% DMSO Extractable total polycyclic aromatic compound (PAC) per IP 346.

COMPONENT	RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED
TOXICOLOGICAL DATA	Carcinogenicity. IP 346: 1.7%
TOXIC DOSE - LD 50	> 5000 mg/kg (oral rat)
TOXIC DOSE - LD 50 SKIN	> 2000 mg/kg (skn rbt)
TOXIC CONC. - LC 50	N/A.
CARCINOGENICITY	The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION There is no ecological data on the product itself.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT HAZARD CLASS	Non-Hazardous (No label required).
U.S. DOT HAZARD LABEL	No DOT label requirement
TDGR CLASS	Not Regulated.
SEA TRANSPORT NOTES	Not regulated per IMDG.
AIR TRANSPORT NOTES	Not regulated per IATA.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

COMPONENT	SARA 302	CERCLA	SARA 313
RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED	No	No	No
OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	No	No	No
LIMESTONE (CALCIUM CARBONATE)	No	No	No
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	No	***	N982 - Zn
DISTILLATES, PETROLEUM, REFINED HEAVY NAPHTHENIC (CAS 64741-96-4 OR 64742-52-5)	No	No	No

REGULATORY STATUS

*** Indicates that no RQ is assigned to this generic or broad class, although the class is a CERCLA hazardous substance. See 50 Federal Register 13456 (April 4, 1985). Values in Section 313 column represent Category Codes for reporting under Section 313.

CLEAN AIR ACT

SARA HAZARD CATEGORIES None

US STATE REGULATIONS

COMPONENT	CA	MA	FL	MN	NJ	PA	RI
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS				Yes	Yes	EH	

STATE REGULATORY STATUS

PROPOSITION 65 REPRODUCTIVE HAZARD: This product may contain the following chemical(s) considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing reproductive toxicity, and for which warnings are now required:

N-Methylpyrrolidone, developmental hazard, CAS# 872-50-4 traces < 35 ppm

PENNSYLVANIA RIGHT-TO-KNOW: This product contains the following chemicals that the state of Pennsylvania has identified as Special Hazardous Substances (SHS), Environmental Hazards (EH), or both (ESHS). The PA regulations require that the MSDS identify all SHS or EH chemicals by chemical name, common name, and CAS Number if they comprise 0.01% or more.

Zinc compounds regulated under CERCLA and SARA 313, Environmental Hazard

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHMIS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

CONTROLLED PRODUCT CLASSIFICATION

Not a controlled product.

GLOBAL INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	PHLPCHN
DISTILLATES, PETROLEUM, REFINED HEAVY NAPHTHENIC (CAS 64741-96-4 OR 64742-52-5)	DSL	Yes	EINECS	Yes	Yes	Yes	Yes Yes

11573 - COUNTRYMARK ADVANTAGE EXTREME TACKY GREASE

RESIDUAL OILS, PETROLEUM, SOLVENT DEASPHALTED	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes
OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	DSL	Yes	EINECS	Yes	2-1416	Yes	Yes	Yes
LIMESTONE (CALCIUM CARBONATE)	Exempt	Yes	EINECS	Yes	1-122	Yes	Yes	Yes
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL NPRI ESTERS, ZINC SALTS		Yes	EINECS	Yes	Yes	Yes	Yes	Yes

CANADA CEPA: All components of this product comply with new substance notification requirements under the Canadian Environmental Protection Act (CEPA).

16. OTHER INFORMATION

NFPA-HMIS HAZARD RATING

HEALTH	Irritation, minor residual injury (1) - HMIS/NFPA
FLAMMABILITY	Burns only if pre-heated (1) - HMIS/NFPA
REACTIVITY	Normally Stable (0) - HMIS/NFPA
PERSONAL PROTECTION INDEX	B - Safety Eyewear and Gloves
REVISION COMMENTS	Section 11: Toxicological Information Section 15: WHMIS
PREPARED BY	Heather Holich James W. Hermann
Replacement of MSDS generated	2004-11-03
DATE	2006-09-05
PRINTING DATE:	2006-09-05
DISCLAIMER	While the information and recommendations set forth herein are believed to be accurate as of the date thereof, the company makes no warranty with respect thereto and disclaims all liability from reliance therein.

* Information revised since previous MSDS version