



CountryMark®

Advantage™

LUBRICANTS

*Pour in the
Advantage...*

Synthetic Blend
Gasoline
Engine Oil

Reduces Wear

Cold Start Lubrication

Improves Cleanliness

...and pour on the miles.

CountryMark's Advantage™ Synthetic Blend Gasoline Engine Oils are formulated using high-quality synthetic base oils and high viscosity index base oils combined with advanced detergent-dispersants, antioxidants, anti-wear agents, friction modifiers, and defoamant additives. These oils provide excellent protection against sludge, engine rust and corrosion under severe low temperatures.

Features and Benefits

Energy Conserving: SAE 5W-20, 5W-30 and 10W-30 meet new fuel economy standards set by API ILSAC GF-4/GF-3.

Pumpability: Due to its unique blend of base stocks, this oil pumps faster from the crankcase to the various engine parts during cold starts, creating less wear.

Durability: Unique Tri-nuclear Molybdenum chemistry is used in these oils. This molybdenum-based chemistry contributes to engine performance and durability by reducing friction and increasing oxidative stability of the oil. Sliding friction and its associated wear, as well as oil thickening due to oxidation, are reduced.

Advanced Wear Protection: These oils offer superior wear protection, as demonstrated in the Sequence VIA performance test.

Rust And Corrosion: Provides superior rust and corrosion protection in the presence of water.

Applications

CountryMark Advantage Synthetic Blend Gasoline Engine Oils are formulated to meet or exceed a variety of specifications and requirements by engine manufacturers, including:

- API SM/SL
- API SJ,SH,SG AND SF (OBSOLETE)
- ILSAC GF-4 (5W-20, 5W-30 AND 10W-30)
- ILSAC GF-3/GF-2 (OBSOLETE)
- FORD (WSS-M2C930) (5W-20)

Contact

For additional information, call CountryMark Technical Support at 1-800-537-5303 and visit us online at www.countrymark.com.

Packaging

Available in quarts, drums, totes & bulk.

Properties	Test	Advantage 5W-20	Advantage 5W-30	Advantage 10W-30	Advantage 10W-40
Viscosity @ 100°C	D445	8.70	10.5	10.3	14.2
Viscosity Index	D2770	150	153	140	148
CCS Viscosity	D5293				
@-30°C (cP max.)		6600	6600	NA	NA
@-25°C (cP max.)		NA	NA	6600	6600
@-15°C (cP max.)		NA	NA	NA	NA
Pour Point °C	D97	-39	-39	-35	-30
Color	D1500	2.5	2.5	2.5	2.5

Get more per gallon.™



CountryMark.