



Terminal Gasoline Specifications⁽¹⁾

VOLATILITY ²	SUMMER April 10 – Sept 15	LOW INTERMEDIATE September 16 – September 30	HIGH INTERMEDIATE March 1 - April 9 October & November	WINTER December - February
RVP, psi ASTM D-5191	9.0 (Max.)	11.5 (Max.)	13.5 (Max)	15.0 (Max.)
CLASS	A-3	C-3	D-4	E-5
Distillation, °F ASTM D-86				
10% (Max.)	158	140	131	122
50% (Min.)	170	170	170	170
50% (Max.)	250	240	235	230
90% (Max.)	374	365	365	365
EBP (Max.)	437	437	437	437
V/L ₂₀ (Min.) ASTM D-4814	140	124	116	105

	84 CBOB	87 REGULAR	87 PLUS ³ E10	89 PLUS ³ E10	91 CBOB	91 PLUS	93 PLUS ³ E10	E85
MOTOR METHOD (Min.)	81.0	82.0	NA	NA	88.0	NA	NA	NA
(R+M) / 2 OCTANE (Min.)	84.5	87.0	87.1	89.2	91.0	91.0	93.4	110.4
Sulfur, ppm (Max.)	80	80	80	80	80	80	80	80
Oxidation Stability, Minutes (Min.)	500	500	800	800	500	800	800	500
Existent Gum, mg/100ml (Max.)	5	5	5	5	5	5	5	5
Copper Strip Corrosion (Max.)	No. 1	No. 1	No. 1	No. 1	No. 1	No.1	No. 1	No. 1
Additives:								
IVD Additive	Present	Present	Present	Present	Present	Present	Present	Present
Oxidation Inhibitor	None	None	Present	Present	None	Present	Present	None
Dye	None	None	None	None	None	None	None	None
TOP TIER	None	None	Present	Present	None	Present	Present	None

¹ CountryMark specifications meet or exceed ASTM automotive specifications.

² Volatility specifications do not apply to gasolines blended with Ethanol.

³ Contains proprietary additive package and 10% Ethanol.