







# Performance Specialties PG 16 - Fuel System Icing Inhibitor

DRI-TEK is used to reduce water contamination in fuel storage tanks; to inhibit bacterial growth; and even to function as a water "anti-freeze" during severe cold temperatures. Petroleum hydrocarbons such as crude oil, lubricating oil, diesel fuel and heating oil can entrain sufficient levels of water to cause operational problems with various equipment. DRI-TEK is a special glycol ether based blend of organic compounds designed to solve problems with water in fuel. Operational malfunctions can begin to occur in diesel equipment when fuel contains as little as 50 ppm entrained water. When water levels exceed 150 ppm, microbial (bacteria) colonization can occur at the fuel/water interface. This contamination can lead to filter plugging, cause equipment failures, and result in corrosive fuel tank damage. Excessive water can freeze at low temperatures and the ice can block filters during vehicle start-up.



### 40CFR80.591 Compliance Statement:

The sulfur content of this diesel fuel additive does not exceed 15 ppm. This is a LEGAL DIESEL™ Fuel Additive Product.

In order to comply with EU regulations (Title II, Chapter 1, Article 8) and to secure documentation to allow this product to be imported into the EU please contact Innospec to join our "Only Representative" and Declaration of Conformity Program.

Technical Support: (302) 454-8100

Customer

Care Center: (800) 441-9547

## **Application**

DRI-TEK should be added directly to the fuel tank just prior to fueling to ensure thorough mixing.

For correcting a severe water contamination problem, add DRI-TEK immediately before fueling for two consecutive fuel-ups.

Monitor your fuel continually for water contamination. Remember that most "fuel pastes" may find pockets of water bottoms, but only a

laboratory analysis can determine the extent of entrained water contamination.

# Personal Safety, First Aid and Storage and Handling

See the Material Safety Data Sheet for product specific information. Ideal storage conditions should offer a clean, dry, indoor location with controlled ambient temperature. Outdoor storage should protect the product from direct sunlight and provide shelter from adverse weather conditions.



# Typical Properties Appearance clear colorless liquid Specific Gravity, $60/60 \,^{\circ}$ ( $15.6^{\circ}$ C) 0.906 Density, Ib/gal, $60 \,^{\circ}$ F, ( $15.6 \,^{\circ}$ C) 7.54 Flash Point, PMCC, $\,^{\circ}$ F ( $\,^{\circ}$ C) 153 (67.2) Pour Point, ASTM D 5950, $\,^{\circ}$ F ( $\,^{\circ}$ C) <-40 (<-40)</td> Viscosity, ASTM D 445, cSt @ 68 $\,^{\circ}$ F ( $20 \,^{\circ}$ C) .4 $0 \,^{\circ}$ F (-17.8 $\,^{\circ}$ C) .14 -20 $\,^{\circ}$ F (-28.9 $\,^{\circ}$ C) .26 Recommended Treat Rate 32 ounces : 250 gallons

